

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date: 06.05.2021

**Version number 5 (replaces version 4)

Revision: 06.05.2021

Page: 1/7

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: Application / Use:

HOCHLEISTUNGSOEL SZ 9850

Industrial lubricant

Article number: 1.2 Relevant identified uses of the substance or mi Application of the substance / the preparation:	Lubricating oil
Uses advised against:	No further relevant information available.
1.3 Details of the supplier of the safety data sheet	
Manufacturer/Supplier:	HERMANN BANTLEON GmbH
	Blaubeurer Strasse 32
	D - 89077 Ulm
	Tel: +49 (0) 731 / 3990-0
	Fax: +49 (0) 731 / 3990-10
Further information obtainable from:	Department: Product safety
	Contact specialist: hse@bantleon.de
1.4 Emergency telephone number:	In case of emergency ONLY:
	During working hours (CET):
	+49 (0) 731 / 39 90 260 or +49 (0) 731 / 39 90 250
	Emergency response (24 hours) CHEMTREC:
	1-800-424-9300 / +1-703-741-5970
	+(44)-870-8200418 (United Kingdom)
	+(44)-203-8073798 (United Kingdom)
	+(31)-858880596 (Netherlands) +(61)-290372994 (Australia)
	0-800-983-611 (South Africa)
	+1 703-527-3887 (USA & Canada)

SECTION 2: Hazards identification

Classification according to Regulation (EC) No 1272/2008	The product is not classified, according to the CLP regulation.
2.2 Label elements	
Labelling according to Regulation (EC) No	
1272/2008	Void
Hazard pictograms	Void
Signal word	Void
Hazard statements	Void
Precautionary statements	P501 Dispose of contents/container in accordance with local regulations.
Additional information:	EUH210 Safety data sheet available on request.
2.3 Other hazards	
Results of PBT and vPvB assessment	
PBT:	Not applicable.
vPvB:	Not applicable.

SECTION 3: Composition/information on ingredients

according to 1907/2006/EC, Article 31

Printing date: 06.05.2021

*

*

**Version number 5 (replaces version 4)

Revision: 06.05.2021

Trade name: HOCHLEISTUNGSOEL SZ 9850

(Contd. of page 1)

Dangerous components:		(Conta.	or page
Base oil, low-viscosity ***)		Asp. Tox. 1, H304	≤2.5%
Additional information:	***) may contain: CAS-numbers (REACh-Registratic 64742-54-7 (01-2119484627-25), 64742-55-8 (01-2 (01-2119480132-48), 64742-65-0 (01-2119471299-2 2119486452-34), 72623-86-0 (01-2119474878-16), 13), 8042-47-5 (01-2119487078-27), 848301-69-9 (The wording of the hazard symbols and H-phrases dangerous ingredients are mentioned. Components with threshold limit values are mention	119487077-29), 64742 27), 68037-01-4 (01- 72623-87-1 (01-21194 01-0000020163-82) is specified in section	74889-
SECTION 4: First aid measures			
4.1 Description of first aid measures			
General information:	Take affected persons out into the fresh air.		
	Position and transport stably in side position.		
After inhalation:	Supply fresh air; consult doctor in case of complain	ts.	
After skin contact:	Immediately wash with water and soap and rinse th		
After eye contact:	Rinse opened eye for several minutes under running		ersist.
	consult a doctor.	5 • • • • 7 • • • • •	,
After swallowing:	Do not induce vomiting; call for medical help immed	liatelv.	
Information for doctor:	Treat symptomatically.	,	
4.2 Most important symptoms and effects, both			
acute and delayed:	No further relevant information available.		
4.3 Indication of any immediate medical attention			
and special treatment needed:	No further relevant information available.		
SECTION 5: Firefighting measures			
5.1 Extinguishing media			
Suitable extinguishing agents:	CO ₂ , sand, extinguishing powder.		
	Use fire extinguishing methods suitable to surround	ina conditions.	
For safety reasons unsuitable extinguishing			
agents:	Do not use water with full jet.		
5.2 Special hazards arising from the substance or			
mixture:	In case of fire, the following can be released:		
inixed of	Nitrogen oxides (NOx)		
	Carbon monoxide (CO)		
	Sulphur oxide (SOx)		
5.3 Advice for firefighters			
Protective equipment:	Wear self-contained respiratory protective device.		
	Do not inhale explosion gases or combustion gases	.	
	Wear fully protective suit.		
Additional information:	Dispose of fire debris and contaminated fire fighting	water in accordance v	vith
	official regulations.		
SECTION 6: Accidental release measures	۱		
6.1 Personal precautions, protective equipment and	d		
emergency procedures	Particular danger of slipping on leaked/spilled produ	ict.	
	Wear protective clothing.		
6.2 Environmental precautions:	Do not allow to enter sewers, surface or ground wat		
····	Prevent from spreading (e.g. by damming-in or oil b	arriers).	
6.3 Mothods and material for containment and			

6.3 Methods and material for containment and cleaning up:

6.4 Reference to other sections

Dispose of the material collected according to regulations.

Absorb with liquid-binding material (sand, diatomite, acid binders, universal

binders, sawdust).

Page: 2/7

See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

according to 1907/2006/EC, Article 31

Printing date: 06.05.2021

**Version number 5 (replaces version 4)

Revision: 06.05.2021

Trade name: HOCHLEISTUNGSOEL SZ 9850

(Contd. of page 2)

SECTION 7: Handling and storage	
7.1 Precautions for safe handling	Store in cool, dry place in tightly closed receptacles.
	No special precautions are necessary if used correctly.
nformation about fire - and explosion protection	: Fire class EN 2: B
Handling:	When handling product in drums use safety footwear and suitable tools. At wor
	please do not eat, drink or smoke.
7.2 Conditions for safe storage, including any inc	compatibilities
Storage:	
Requirements to be met by storerooms and	
receptacles:	Store only in the original receptacle.
	Provide floor trough without outlet.
	Prevent any seepage into the ground.
	Use only receptacles specifically permitted for this substance/product.
nformation about storage in one common storag	Je
facility:	Store away from foodstuffs.
	Store away from oxidising agents.
	Store away from water.
Further information about storage conditions:	Recommended storage temperature: 5 to 40 °C.
Shelf life from date of dispatch:	Maximum 3 years
7.3 Specific end use(s):	For more information see technical information.
SECTION 8: Exposure controls/persona	I protection

	be kept at the lowest possible level.
8.2 Exposure controls	
Appropriate engineering controls	No further data; see section 7.
Individual protection measures, such as person	nal protective equipment
General protective and hygienic measures:	The usual precautionary measures are to be adhered to when handling chemicals.
	Wash hands before breaks and at the end of work.
	Avoid close or long term contact with the skin.
Respiratory protection:	No respiratory protection is ordinarily required under normal conditions of use.
	Select a filter suitable for combined particulate/ gases and organic vapours (boiling
	point > 65 ° C, AP2, EN 14387), if exposure limit is exceeded or when aerosol or
	mist is formed.
Hand protection	Safety gloves of nitrile rubber or viton.
	Preventive skin protection by use of skin-protecting agents is recommended.
Material of gloves	Fluorocarbon rubber (Viton)
	Nitrile rubber, NBR
	The selection of the suitable gloves does not only depend on the material, but also
	on further marks of quality and varies from manufacturer to manufacturer. As the
	product is a preparation of several substances, the resistance of the glove material
	can not be calculated in advance and has therefore to be checked prior to the
	application.
Penetration time of glove material:	The exact break trough time has to be found out by the manufacturer of the
	protective gloves and has to be observed.
	Value for the permeation: Level = 6 (480 min)
Eye/face protection	Goggles recommended during refilling.
Dealer was to attain a	Durate atting sounds, all this s

Protective work clothing.

**Version number 5 (replaces version 4)

Trade name: HOCHLEISTUNGSOEL SZ 9850

Revision: 06.05.2021

(Contd. of page 3)

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties	
General Information	
Physical state	Fluid
Colour:	Black
Odour:	Mild
Odour threshold:	Not determined.
Melting point/freezing point:	Not determined.
Boiling point or initial boiling point and boiling range	Not determined.
Flammability	Not applicable.
Lower and upper explosion limit	
Lower:	0.9 Vol % (typ.)
Upper:	7.0 Vol % (typ.)
Flash point:	>180 °C (DIN EN ISO 2592)
Auto-ignition temperature:	Not determined.
Decomposition temperature:	Not determined.
pH Missosity	Not determined.
Viscosity:	40 mm ² / ₂ (DIN E4 500)
Kinematic viscosity at 40 °C	46 mm²/s (DIN 51 562)
Dynamic:	Not determined.
Solubility	N I a fear the still have an elifett as the fear sector
water:	Not miscible or difficult to mix.
Partition coefficient n-octanol/water (log value)	Not determined.
Vapour pressure:	Not determined.
Density and/or relative density	
Density at 15 °C:	0.876 g/cm ³ (DIN 51 757)
Relative density	Not determined.
Vapour density	Not determined.
9.2 Other information	
Appearance:	
Form:	Fluid
Important information on protection of health and environm	nent,
and on safety.	
Explosive properties:	The product shows no danger of explosion, but it may build explosive
	mixtures with air (by vaporisation, oil mist formation, heating above the
	flash point).
Change in condition	
Drip point:	Not determined.
Pour point:	≤ -21 °C (DIN ISO 3016)
Evaporation rate	Not determined.
Information with regard to physical hazard classes	
Explosives	Void
Flammable gases	Void
Aerosols	Void
Oxidising gases	Void
Gases under pressure	Void
Flammable liquids	Void
Flammable solids	Void
Self-reactive substances and mixtures	Void
Pyrophoric liquids	Void
Pyrophoric solids	Void
Self-heating substances and mixtures	Void
Substances and mixtures, which emit flammable gases in	
	Void
contact with water	Void
contact with water Oxidising liquids	Void
contact with water	

Page: 5/7

Trade name: HOCHLEISTUNGSOEL SZ 9850

Corrosive to metals Desensitised explosives	Void Void
SECTION 10: Stability and reactivity	
10.1 Reactivity	See 10.2 to 10.6
10.2 Chemical stability:	Stable at normal conditions.
Thermal decomposition / conditions to be avoided:	Avoid contact with heat, sparks, flames and all other sources of ignition.
10.3 Possibility of hazardous reactions:	Reacts with strong oxidising agents.
10.4 Conditions to avoid	No specific data available.
10.5 Incompatible materials:	No further relevant information available.
10.6 Hazardous decomposition products:	No dangerous decomposition products known.
Additional information:	Product is not classified as inflammable but can burn.
SECTION 11: Toxicological information	
11.1 Information on hazard classes as defined in	
Regulation (EC) No 1272/2008	These statements are based on data for components of the material or for simila
	materials.
Acute toxicity	Based on available data, the classification criteria are not met.
LD/LC50 values relevant for classification:	
Base oil, low-viscosity ***)	
Oral LD50 >5,000 mg/kg (rat) (OECD 401)	
Dermal LD50 >5,000 mg/kg (rabbit) (OECD 402)	
Skin corrosion/irritation	Based on available data, the classification criteria are not met.
Serious eye damage/irritation	Based on available data, the classification criteria are not met.
by inhalation:	No irritant effect expected.
Respiratory or skin sensitisation	Based on available data, the classification criteria are not met.
Germ cell mutagenicity	Based on available data, the classification criteria are not met.
Carcinogenicity	Based on available data, the classification criteria are not met.
Reproductive toxicity	Based on available data, the classification criteria are not met.
STOT-single exposure	Based on available data, the classification criteria are not met.
STOT-repeated exposure	Based on available data, the classification criteria are not met.
Aspiration hazard	Based on available data, the classification criteria are not met.
Subacute to chronic toxicity:	Prolonged and/or repeated contact may cause defatting of the skin which can lea
-	to dermatitis and may make the skin more susceptible to irritation and penetratic
	by other materials.
Additional toxicological information:	The product is not subject to classification according to the calculation method o
	the General EU Classification Guidelines for Preparations as issued in the latest
	version.
	When used and handled according to specifications, the product does not have
	any harmful effects to our experience and the information provided to us.

12.1 Toxicity

•		
Aquatic toxicity:		
Base oil, low-viscosity ***)		
EC50/48h >10,000 mg/l (Daphnia magna)	EC50/48h >10,000 mg/l (Daphnia magna)	
LC50/96h >100 mg/l (Pimephales promelas) (O	LC50/96h >100 mg/l (Pimephales promelas) (OECD 203)	
NOEC/21d >10 mg/l (Daphnia magna)		
12.2 Persistence and degradability	No further relevant information available.	
12.3 Bioaccumulative potential	No further relevant information available.	
12.4 Mobility in soil	The product is not soluble in water. If it enters soil, it will adsorb to soil particles and will not be mobile.	
12.5 Results of PBT and vPvB assessment		
PBT:	Not applicable.	
vPvB:	Not applicable.	
12.6 Endocrine disrupting properties	The product does not contain substances with endocrine disrupting properties. (Contd. on page 6)	

**Version number 5 (replaces version 4)

Revision: 06.05.2021

Page: 6/7

Trade name: HOCHLEISTUNGSOEL SZ 9850

	(Contd. of page
12.7 Other adverse effects:	
Additional ecological information:	
General notes:	Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardou for water
	Do not allow product to reach ground water, water course or sewage system.
SECTION 13: Disposal considera	tions
13.1 Waste treatment methods	
Recommendation	Must not be disposed together with household garbage. Do not allow product to reach sewage system.
European waste catalogue	The recommended waste code refers to the product as delivered.
	The assignment of the waste code number according to the application is to be
	conducted in individual cases by the waste producer based on the European
	Waste Code Catalogue in coordination with the regional disposal company and
	with aspects specific to the sector and process in mind.
12 01 07* mineral-based machining oils free	e of halogens (except emulsions and solutions)
I	
Uncleaned packaging:	Empty packing completely. Handover to authorized disposal company.
Recommendation:	Disposal must be made according to official regulations.

and proper cleaning.

Empty contaminated packagings thoroughly. They may be recycled after thorough

SECTION 14: Transport information

14.1 UN number or ID number	
ADR, IMDG, IATA	Void
14.2 UN proper shipping name	
ADR, IMDG, IATA	Void
14.3 Transport hazard class(es)	
ADR, IMDG, IATA	
Class	Void
14.4 Packing group	
ADR, IMDG, IATA	Void
14.5 Environmental hazards:	
Marine pollutant:	No
14.6 Special precautions for user	Not applicable.
14.7 Maritime transport in bulk according to IMO instruments	Not applicable.
UN "Model Regulation":	Void

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II		
None of the ingredients is listed.		
REGULATION (EU) 2019/1148		
Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))		
None of the ingredients is listed.		
Annex II - REPORTABLE EXPLOSIVES PRE	CURSORS	
None of the ingredients is listed.		
National regulations:		
Waterhazard class:	Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water	
15.2 Chemical safety assessment:	A Chemical Safety Assessment has not been carried out.	

**Version number 5 (replaces version 4)

Revision: 06.05.2021

Trade name: HOCHLEISTUNGSOEL SZ 9850

(Contd. of page 6)

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Recommendation of the manufacturer:

Absorb spilled liquid media with AVILUB SUPER-SORB and dispose in acccordance with local regulations. For skin protection when handling water-mixable and not-water-mixable media we recommend application of COVER SKIN.

Relevant phrases	H304 May be fatal if swallowed and enters airways.
Department issuing SDS:	Department: Product safety
Contact:	hse@bantleon.de
Abbreviations and acronyms:	ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent VPVB: very Persistent and very Bioaccumulative Asp. Tox. 1: Aspiration hazard – Category 1

* Data compared to the previous version altered.

**Information about the version number:

Replaces all previous versions.